Albany/Troy 3000 S DFFICE OF THE MARION COUNTY SURVEYOR SECTION RECORD CORNER 15 RANGE -29 TOWNSHIP 15 -5-30-0111-17-06 SECTION _ PARTY CHIEF: Kiste Wilcoxen 0 CREW: -V TYPE OF MARKER: Harrison /Perkins METHOD OF ESTABLISHMENT: ____County: 5-13-96 IN. S.P.C. E ZONE, NAD 83 NAME: 15042902 N: 496887.7026(m) E: 61881.9053(m) 25th/ H 2. 7. 60.001 Troy/Albany 3000 S_ 25th/Perkins 3200 125.40' 100.12. 6. 3.

Original post set 1820 by Hendricks with witnesses: 16" ash N 80 W 32 links; 22" ash S 79 E 24 links. Corner tied by Scherschel on 5-15-63 and called a cut cross. 6-10-56 Monroe re-tied corner and called it a road nail. 2-17-77 Miller called the same. 3-16-89 Wilcoxen called a PK nail. 9-25-89 corner excavated and Harrison set. Re-tied 5-13-96 by Whiteside. Re-tied 5-30-01 by Kiste.

15042902

15042902			
REF.	DISTANCE	DESCRIPTION	
1.	71.88'	PK nail W PwP#243-641 A 12"up	
2.	55.66	Top nut of fire hydrant	
3.	125.40'	NE corner of apartment building: brick	
4.	54.38'	Cut 'x' SW-bolt of traffic signal pole base	
5.	100.12	NW corner of apartment building : brick	
6.	58.85	PK nail S PwP#83-640 B 4"up	
7.	60.00'	Cut 'x' NE-bolt of traffic signal pole base	